

# Yoshida Tools

## FLUX CHIPPER YFC Series

*Light weight, Powerful and Durable*

*High Blow frequency (90Hz)*

*Low Air Consumption*

*Providing high working efficiency*

*Direction of Chisel is easily adjusted (YFC-1)*

*Chisel can be easily exchanged (YFC-2)*



YFC-1L

176mm



YFC-2L

182mm



SAFETY LEVER

### Specification

Model	Throttle Type	Blows Hz	Piston Diameter mm	Stroke mm	Overall Length mm	Max Dia	Mass kg	Max Air Consumption Nm <sup>3</sup> /min	Air Hose Size mm	Air Inlet Thread
						mm				
YFC-1L	Lever	90	20	16	176	36	0.8	0.14	6.3	RC-1/4
YFC-1F	Safety Lever	90	20	16	176	36	0.8	0.14	6.3	RC-1/4
YFC-2L	Lever	90	20	16	182	36	0.99	0.14	6.3	RC-1/4
YFC-2F	Safety Lever	90	20	16	182	36	0.99	0.14	6.3	RC-1/4

Standard Accessory: NL-22PM Coupler Plug

Chisel Shank Size: (YFC-1)  $\phi$  11x20, (YFC-2)  $\phi$  12x25

## YOSHIDA MFG.CO.,LTD

3-36-3 Yamaga-cho, Yao-city, Osaka, Japan 581-0812

TEL +81-72-996-5673

FAX +81-72-997-9416

E-mail: [info@yoshida-mfg.co.jp](mailto:info@yoshida-mfg.co.jp)



※Specifications are subjects to change without notice.

YOSHIDA MFG.CO.,LTD.

2013.03