

HORIZONTAL GRINDERS



UG-1250L-72



UG-1250-72



UG-1500L-60




UG-1500-60



UG-2000L-45

Heavy-Duty Type (Governed)

- Two speeds are available for UG-1500 and UG-2000 series.
(Higher speed for resinoid wheels and lower speed for vitrified wheels)
- Two different Throttle Handles are available for every model.
- Lever Type Handles are recommended for safer operation.



WHEEL SIZE

Model Name	Thickness
UG-1200 Series	13-19mm
UG-1500 Series	18-25mm
UG-2000 Series	19-25mm

SPECIFICATIONS

Recommended Air Pressure : 0.6MPa (85psi)

Model	Capacity (Wheel Size)		Max.Free Speed (about)	Rated Horse Power	Overall Length (about)		Weight less wheel (about)		Spindle Size	Air Inlet Thread (Pipe Tap)	Air Hose Size		Average Air Consumption	
	mm	in			mm	in	kg	lb			mm	in	m ³ /min	ft ³ /min
UG-1250-72	125	5	7200	750	436	17 11/64	3.20	7.04	1/2-13	NPT3/8	12.7	1/2	0.90	32.7
UG-1250L-72	125	5	7200	750	436	17 11/64	2.80	6.16	1/2-13	NPT3/8	12.7	1/2	0.90	32.7
UG-1500-60	150	6	6000	1320	497	19 9/16	4.88	10.74	5/8-11	NPT3/8	12.7	1/2	1.30	45.9
UG-1500-41	150	6	4100	975	497	19 9/16	4.88	10.74	5/8-11	NPT3/8	12.7	1/2	1.30	45.9
UG-1500L-60	150	6	6000	1320	495	19 31/64	4.62	10.16	5/8-11	NPT3/8	12.7	1/2	1.30	45.9
UG-1500L-41	150	6	4100	975	495	19 31/64	4.62	10.16	5/8-11	NPT3/8	12.7	1/2	1.30	45.9
UG-2000L-45	200	8	4500	1500	520	20 15/32	5.30	10.16	5/8-11	NPT3/8	12.7	1/2	1.55	54.7
UG-2000L-31	200	8	3100	1260	520	20 15/32	5.30	11.62	5/8-11	NPT3/8	12.7	1/2	1.55	54.7

* Do not use vitrified wheels with higher speed type of each model.