

**AIR ANGLE GRINDER**



- Horse Power : 1 HP
- Powerful air motor maintains RPM under heavy load
- Removable side handle
- Guard/ Wheel flange set included M10\*1.5 male threaded spindle
- Safety throttle lever optional

**SPECIFICATION (air pressure at 90psi 、 6.2 bar 、 6.3 kg/cm<sup>2</sup> )**

MODEL	Pad Size		Free Speed	Spindle Thread	Air Consumption		Overall Length		Air Inlet	Net Weight		Sound Level
	mm	inch	rpm		l/min	cfm	mm	inch	P.T	kg	lb	dB(A)
<b>OP-AG704-4</b>	100	4	10,000	M10*1.5	184	6.5	185	7.3	1/4	1.15	2.53	81

## Air Angle Grinder

### 氣動角磨機



**OP-1851** 4"  
Side exhaust  
側排氣



**OP-2850** 4"  
**OP-2850A** 5"  
Front exhaust  
前排氣



**OP-3856** 7"  
Side exhaust  
側排氣



**OP-1851A** 4"  
Side exhaust  
側排氣



**OP-1850** 4"  
**OP-1850A** 5"  
Front exhaust  
前排氣



**OP-3855** 7"  
Side exhaust  
側排氣

### SPECIFICATION (air pressure at 90psi \ 6.2bar \ 6.3kg/cm<sup>2</sup>)

MODEL 型號	Pad Size 尺寸		Spindle Thread 主軸牙數	Free Speed 無負荷轉速	Air Consumption 耗氣量		Overall Length 全長		Air Inlet 入氣接頭	Net Weight 重量		Hose Size 風管尺寸		Motor Power 馬達功率	
	mm	inch			mm	rpm	l/min	cfm		mm	inch	P.T	kg	lb	mm
OP-1851	101	4		10500	283	10	165	6.49	1/4	1	2.2	9.5	3/8	246	0.33
OP-2850	101	4	M10x1.5	11000	452	16	235	9.25	1/4	1.8	3.96	9.5	3/8	470	0.63
OP-2850A	127	5	M14x2	10000	452	16	235	9.25	1/4	1.88	4.14	9.5	3/8	470	0.63
OP-3856	177	7		7000	791	28	290	11.41	3/8	3.31	7.29	9.5	3/8	895	1.2
OP-1851A	101	4		10500	283	10	145	5.7	1/4	1	2.2	9.5	3/8	246	0.33
OP-1850	101	4	M10x1.5	11000	452	16	245	9.65	1/4	1.71	3.76	9.5	3/8	470	0.63
OP-1850A	127	5	M14x2	10000	452	16	245	9.65	1/4	1.8	3.96	9.5	3/8	470	0.63
OP-3855	177	7		7000	791	28	345	13.58	3/8	3.31	7.29	9.5	3/8	895	1.2



**OP-845P** 4"  
Rear exhaust  
Spindle Thread 3/8"-24UNF  
後排氣



**OP-CVG660B** 6"  
Vertical grinder  
垂直型角磨機



**OP-CVG945B** 9"  
Vertical grinder  
垂直型角磨機

### SPECIFICATION (air pressure at 90psi \ 6.2bar \ 6.3kg/cm<sup>2</sup>)

MODEL 型號	Pad Size 尺寸		Free Speed 無負荷轉速	Air Consumption 耗氣量		Overall Length 全長		Air Inlet 入氣接頭	Net Weight 重量		Hose Size 風管尺寸		Motor Power 馬達功率	
	mm	inch		rpm	l/min	cfm	mm		inch	P.T	kg	lb	mm	inch
OP-845P	101	4	12000	396	14	303	11.92	1/4	1.5	3.3	9.5	3/8	746	1
OP-CVG660B	150	6	5500	580	20.5	279	10.98	1/2	6.29	13.86	12.7	1/2	2835	3.8
OP-CVG945B	230	9	4500	580	20.5	279	10.98	1/2	6.05	13.33	12.7	1/2	2835	3.8