DP-637TT

Reversible Airless tips & tip gasket combo kit
Stainless steel shank + Tungsten carbide orifice
Nylon + stainless steel tip gasket, Durable and easily reversed for cleaning.
Tip Shank Diameter: 11.1mm
Max.5000 PSI (345 BAR)
This tip could fit Titan, Wagner, ASM, Airlessco etc.
Most kind of airless guns.
Guaranteed perfect quality, fine atomization. Over 5000 m2 lifetime.
Tip size available: from 0.011" to 0.035" (2xx to 6xx)
Best quality, best selling.



DP-637G

DP-637T5

Reversible Airless tips & tip gasket combo kit
Airless tip in RAC V type, used for old Graco guns.
Stainless steel shank + Tungsten carbide orifice
Nylon + stainless steel tip gasket, Durable
and easily reversed for cleaning.
Tip Shank Diameter: 11.1mm
Max.5000 PSI (345 BAR)
Tip size available: from 0.011" to 0.035" (2xx to 8xx)





Blister Package

DP-637TX

Reversible Airless tips & tip gasket combo kit
Airless tip in RAC X type, used for new Graco contractor guns.
Stainless steel shank + Tungsten carbide orifice
New material tip gasket, for easily reversed for cleaning.
Tip Shank Diameter: 11.4mm
Max.5000 PSI (345 BAR)
Guaranteed perfect quality, fine atomization. Over 5000 m2 lifetime.
Tip size available: from 0.011" to 0.035" (2xx to 6xx)





DP-637TW

DP-637TL

LineLaser road marking tips
1708&1908 with width 14cm specially for road line marking

Creates clean, laser-sharp lines with no fuzzy edges or thin spots
Designed specifically for parking lots, roads, warehouse floors, crosswalks and athletic fields
Ensures consistent paint thickness, from edge to edge, less overspray and long-lasting lines Sprays heavy water-base to thin alkyd traffic paints





DP-637XHD
(500bar)

Chart for airless tips

Orifice Size	Fan Width - Inches									Flow Rate		Application	Filter
inch	2" -4" Fan	4" -6" Fan	6" -8" Fan	8" -10" Fan	10" -12" Fan	12" -14" Fan	16" -18" Fan	24" -26" Fan	4"-6" Fan	gpm	L/min		
0.011"	111	211	311	411						0.12	0.45	Stain or Lacquer	150mesh (red)
0.013"	113	213	313	413	513	613				0.18	0.68		
0.015"	115	215	315	415	515	615				0.24	0.91	Oil Base Paint	100mesh (yellow)
0.017"	117	217	317	417	517	617			1708	0.31	1.17	Latex Paint / Acrylic / Enamel	100mesh (yellow)
0.019"	119	219	319	419	519	619	819	1219	1908	0.38	1.44		60mesh (white)
0.021"	121	221	321	421	521	621	821	1221		0.47	1.78		
0.023"		223	323	423	523	623	823	1223		0.57	2.16	Heavy latex	60mesh (white)
0.025"		225	325	425	525	625	825	1225		0.67	2.54		
0.027"		227	327	427	527	627	827	1227		0.77	2.91		
0.029"		229	329	429	529	629	829	1229		0.9	3.41	Elastomeric / Blockfiller / Primer	30mesh (green)
0.031"		231	331	431	531	631	831	1231		1.03	3.9		
0.033"		233	333	433	533	633	833	1233		1.17	4.43		
0.035"		235	335	435	535	635	835	1235		1.31	4.96		
		237	337	437	537	637					3.41		
		239	339	439	539	639					3.9		
		241	341	441	541	641					4.43		
		243	343	443	543	643					4.96		
				445	545	645					3.41		
				447	547	647					3.9		
				449	549	649					4.43		
				451	551	651					4.96		
				453	553	653					4.43		
				455	555	655					4.96		

Example: For a tip with a .017" orifice and a 10" - 12" fan pattern, order DP637T-517 Reversible Tip. Fan width of a spray pattern is measured at 12" from the surface.