



**R-77-B G**  
Gravity  
With RC-4R-B Cup



**R-413-B G**  
Gravity  
With RC-6M-B Cup

## Functions and Characteristics

- ◆ Light weight forged aluminium gun body provides better control of operation. Anodizing and sand blasting surface is easy to clean and maintain.
- ◆ Provide finer atomization and homogeneous spray pattern, reduce over spray perfectly in low air pressure.
- ◆ Nozzle and needle are made of stainless steel, suitable for water-based paints.

Model	Type of feed	Nozzle size	Air cap	Air pressure	Air consumption	Fluid output	Spray width ±20	Weight	
		ømm (in)		kg/cm <sup>2</sup> (Mpa)	l/min(cfm)	ml/min	mm(in)	g(lbs)	
R-77-B-G15	Gravity	1.5(0.059)		3.0-3.5 (0.29-0.34)	290(10.25)	270	290(11.42)	590(1.3)	
R-77-B-G20		2.0(0.079)			360(12.72)	440	320(12.60)		
R-77-B-G25		2.5(0.098)			460(16.25)	520	330(13)		
R-413-B-G12	Gravity	1.2(0.047)	LV2	2.0-3.0 (0.2-0.29)	320(11.3)	160	230-250(9.06-9.84)	690 (1.52)	
R-413-B-G13		1.3(0.051)	LV2		320(11.3)	180	240-260(9.45-10.24)		
R-413-B-G14		1.4(0.055)	LV2		320(11.3)	215	250-275(9.84-10.82)		
R-413-B-G15		1.5(0.059)	LV2		320(11.3)	270	260-280(10.24-11.02)		
R-413-B-G16		1.6(0.063)	LV2		320(11.3)	275	300-340(11.81-13.39)		
R-413-B-G18		1.8(0.071)	LV2		320(11.3)	330	330-335(12.99-13.98)		
R-413-B-G20		2.0(0.079)	LV2		320(11.3)	390	320-365(12.60-14.37)		
R-413-B-G25		2.5(0.098)	W2		2.5-3.0(0.24-0.29)	360(12.72)	510		320(12.60)

◆R-77-B Spraying distance: 250mm (9.84in). Fluid viscosity: 20±1 second/ RV-2. Coating pressure: 0.8kg/cm<sup>2</sup>. Fluid inlet: 3/8 PF/NPF. Air inlet: 1/4 PF/NPF.

◆R-413-B Spraying distance: 250mm (9.84in). Fluid viscosity: 20±1 second/ RV-2. Fluid inlet: M16X1.5P. Air inlet: 1/4 PF/NPF.