



R-3200
Pressure

R3300(ø1.7)
Spray pattern



R-3300
Gravity
With RC-6M Cup
(RC-6DC G1 Cup)

Functions and Characteristics

- ◆ R-3200 is a high-pressure spray gun with air pressure range 3.0-4.0kg/cm²; it is suitable for both large-area continuous rapid spraying and high viscosity, coarse-grained paint, water-based paint or ceramic glaze spraying ect.
- ◆ The spray pattern is longer and wider than traditional spray gun, and have large fluid output with MAX (1500ml/min). Therefore it is suitable for industries of ceramic, furniture, construction, shipbuilding ect .
- ◆ R-3300 This spray gun provide fine atomization, wider spray pattern suitable for automotive industries.
- ◆ R-3300 Nozzle and needle are made of high quality stainless steel, suitable for water base paint and solvent.

Model	Type of feed	Nozzle size	Air pressure	Air consumption	Fluid output	Spray width ±20	Weight
		ømm (in)	kg/cm ² (Mpa)	l/min(cfm)	ml/min	mm(in)	g(lbs)
R-3200	Pressure	1.8(0.071)	3.0-4.0 (0.29-0.39)	450-460 (31.4-31.7)	1500	350-360 (13.78-14.17)	566 (1.25)
R-3300-G10	Gravity	1.0(0.039)	3.5-4.0 (0.34-0.39)	380(13.43)	220	200(7.87)	515(1.36)
R-3300-G13		1.3(0.051)			300	220(8.66)	
R-3300-G14		1.4(0.055)			320	235(9.25)	
R-3300-G15		1.5(0.059)			340	250(9.84)	
R-3300-G17		1.7(0.067)			400	280(11.02)	
R-3300-G20		2.0(0.078)			480	310(12.20)	

◆ R-3200 Spraying distance: 200mm (7.87in). Fluid viscosity: 14-40 ±1 second/ RV-2. Fluid inlet: 3/8PF/NPF. Air inlet: 1/4 PF/NPF.

◆ R-3300 Spraying distance: 250mm (9.84in). Fluid viscosity: 20±1 second/ RV-2. Fluid inlet: M16X1.5P. Air inlet: 1/4 PF/NPF.